

SPECIALTY FILM & SHEET

SABIC's Specialty Film & Sheet business of Innovative Plastics strategic business unit is a leading, global supplier of engineering thermoplastics LEXANTM film and sheet with an 80-year history of breakthrough solutions that solve its customers' most pressing challenges. Today, Innovative Plastics is a multi-billion-dollar company with operations in more than 35 countries and approximately 9,000 employees worldwide. The company continues to lead the plastics industry with customer collaboration and continued investments in new polymer technologies, global application development, process technologies, and environmentally responsible solutions that serve diverse markets such as automotive, electronics, building & construction, transportation, and healthcare.

LEXANTM Sheet Portfolio









General Purpose

Products

- LEXANTM 9030 / 9034 / 9030 TG sheet
- LEXANTM FR UL 94 V2 clear sheet
- LEXANTM EXELLTM-D ST textured sheet
- LEXANTM 2-side UV protected sheet EXELLTM-D, XL102UV

Standard Colors#

Transparent: Clear, Bronze, Grey, White

Standard Sizes#

Sheet size: Width: 1000 mm, 1220 mm, 2050 mm

Thickness: 0.75 mm - 15.0 mm (Thickness range may vary per product)

High Abrasion Resistant

Products

- LEXANTM MARGARDTM sheet 2 side coated -MR5E, MR10, MRX
- LEXANTM MARGARDTM sheet 1 side coated -MR51, MR101LG,
- LEXAN™ MARGARD™ sheet High OQ 1 side coated - HLG5, HLGA3
- Formable LEXAN™ MARGARD™ sheet FMR5XT, CTGXTAF, MRFAF

Standard Colors#

Transparent: Clear, Bronze, Grey, Green

Standard Sizes#

Sheet size: Width: 1220 mm, 2050 mm Thickness: 0.75 mm - 12.7 mm

Optical Quality

Products

- LEXANTM 9034HO / 9034LG sheet Improved Optical Quality sheet
- LEXANTM ULG1003 sheet Highest Quality Optical Quality sheet
- LEXAN™ SL2030 sheet Optical Quality thin gauge

Standard Colors#

Transparent: Clear

Standard Sizes#

Sheet size: Width: 1220 mm, 2050 mm Thickness: 0.75 mm - 12.7 mm

Sign – UV Protected

Products

- LEXANTM UV protected sheet SGC100, SG410, SP24
- LEXANTM Optical Bright sheet with LED light hiding power; SG305-OB, EXELLD-OB

Standard Colors#

Opal White

Standard Sizes#

Sheets and coils/spools available Thickness: 1.5 mm - 6 mm

Colors; Widths; Textures; Thickness

Varies by grade and FR/FSY standard

FR & Opaque

Products

- LEXANTM Transparent Uncoated sheet F2000, F2000A, F2500
- LEXANTM Opaque Uncoated sheet F6000, H6000, ETFR
- LEXANTM Opaque Copolymer sheet H6300, XHR6000
- ULTEMTM Opaque sheet 1613V, 1668A

Standard colors and sizes may vary by product. Additional colors and dimensions may be available with minimum order quantity.